



Markets

- material handling
- building automation & security
- transportation
- distribution

Applications

- forklifts
- alarm devices
- speciality vehicles
- international catalog distributors

Preferred range

Partnumber	Terminal	Actuator	Electrical rating @	
			ENEC	UL/CSA
V3SUL	prewired 0.5M	plunger	250 VAC 5 10 (4) A, 25E3 A	125/250 VAC 5 10 A A
V3SY1UL	prewired 0.5M	plain lever 26.2 mm	250 VAC 5 10 (4) A, 25E3 A	125/250 VAC 5 10 A A
V3SYRUL	prewired 0.5M	roller lever 11.7 mm	250 VAC 5 10 (4) A, 25E3 A	125/250 VAC 5 10 A A
V3SYR1UL	prewired 0.5M	roller lever 24.2 mm	250 VAC 5 10 (4) A, 25E3 A	125/250 VAC 5 10 A A

Product type	■ Burgess Sealed Miniature Micro switch
Dimensions	■ 32 x 24 x 10 mm
Characteristics	<ul style="list-style-type: none"> ■ sealed IP67 ■ flying leads ■ robust construction
Rating	■ 250 VAC, 5 A
Actuators	<ul style="list-style-type: none"> ■ plunger ■ plain lever ■ roller lever
Approvals	<ul style="list-style-type: none"> ■ ENEC ■ UL ■ CSA
Typical markets	<ul style="list-style-type: none"> ■ material handling ■ building automation & security ■ transportation ■ distribution
Typical applications	<ul style="list-style-type: none"> ■ forklifts ■ alarm devices ■ speciality vehicles ■ international catalog distributors