

A

B

C

D

E

F


G

H

I

X

Contact blocks

		Cat. no.	Ref. no.
Logic Reed	Contact type	NC	P9B01FH 187014
		NO	P9B10FH 187015
A new range of LOGIC REED contact blocks with faston terminals for use with power lower than 12V - 5mA.	Rated voltage	AC2 to 120V max. DC2 to 30V max.	
	Rated current	AC/DC - 0.001 to 0.15A max.	
	Rated power	AC - 8VA max. DC - 4.5W max.	
	Minimum centerline distance	30x32 mm.	
	Mounting on operators	through specific bayonet flange adaptor.	P9ACFSM 187846
	Full voltage power supply		P9PDHF 187056

With screw



min. 1 of 22 AWG (0.32 mm²)
max. 2 of 12 AWG (3.3 mm²)













Faston



1 x (6.35 x 0.8 mm)
2 x (2.8 x 0.8 mm)

Terminal adapter
printed circuit board
adapter

		Contact type	Cat. no.	Ref. no.
				
		NC+NO	P9B11VN	187000
		NC+NC	P9B02VN	187008
		NO+NO	P9B20VN	187009
		NC	P9B01VN	187001
		NO	P9B10VN	187002
		NC late opening	P9B01VR	187003
		NO early closing	P9B10VA	187004
		NC	P9B01FN	187012
		NO	P9B10FN	187013
			P9ACA6	188804

The catalogue numbers in **bold** are available from stock.